

Survey of Section T. 7 R. 1 E



FIELD NOTES.

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
A {	Boak	10	S 43° W	38			
	W oak	6	N 79° W	16 1/2			
B {	Walnut	12	N 86 1/2° W	126			
	oak	12	N 15 1/2° W	172			
C {	oak	4	S 17° E	18 3/4			
	oak	3	S 61° E	37 1/2			
D {	oak	6	S 28° E	16 1/2			
	oak	7	N 45 1/2° E	20 1/2			
E							
F							
G							
H							

Aug 18 1908 adj. & am. law & notice having been given
to the interested parties we met on above date
and organized by appointing George Cox
Alexander Young, Etienne or George Follette
Hagman

We then proceeded to make the following
survey in section 7 S 7 R 1 E as per plat and
notes

Reestablished the center of said section
by marking new witnesses Buck 10 m S 45° W -
38 lbs W 2 1/2 in V 77° W 16 1/2 lbs

Established a stone at the distance between
the center and S 1/2 m p, said section witnessed by
B walnut 12 in V 86 1/2° W 126 lbs Sugar 12 in V 154° W 172 lbs

Established a stone at the distance between
the center of the S. W. quarter and the S 1/4 m p
of said section witnessed by W walnut 4 in
S 17° E 18 1/2 lbs W walnut 6 m S 65° E 67 1/2 lbs

Established a stone at the center of the S. W.
quarter of said section witnessed by
M hony 6 in S 28° E 16 1/2 lbs Buck 7 m V 48 1/2° E 20 1/2 lbs

I hereby certify the foregoing to be a true and
correct report of the survey made by me on
above date as I verily believe. In witness
whereof I attach my hand and seal

G. H. Bowers